

Locking Devices, Industrial, Female Connector Body, 30A 125/250V, 3-Pole 4-Wire Grounding, L14-30R, Screw Terminal, Black and White

By Bryant
Catalog # [71430NC](#)



Locking Devices, Industrial, Female Connector Body, 30A 125/250V, 3-Pole 4-Wire Grounding, L14-30R, Screw Terminal, Black and White

Features

- Face and body feature alignment keys for easy assembly
- Amperage, voltage and NEMA configuration imprinted on face for easy identification
- Impact/chemical resistant, toughened nylon construction
- Internal “self-centering” Triple Gripper® cord grip with “radius teeth” design provides secure cord retention

Application

Heavy Duty Industrial

Specifications

| | |
|------------------------------------|---|
| Environmental Conditions | Indoor Dry Unless Protected By Additional Means |
| EU RoHS Indicator | Yes |
| Standards - RoHS Compliance Status | CM |
| Nema Rating | L14-30R |

Conductor

| | |
|----------------------|-------------------|
| Number Of Wires | 4-Wire |
| Wire Size | #18 AWG to #8 AWG |
| Number Of Conductors | 4-Wire Grounding |
| Conductor Range | #12 AWG to #8 AWG |
| Number Of Poles | 3-Pole |

Current

| | |
|----------------------------|-----------------|
| Current/Amperage Rating | 30 Amp |
| Description | |
| Current Rating | 30 A |
| Amperage Rating | 30 A |
| Voltage Rating Description | 125/250 VAC |
| Connectivity | Screw Terminals |

Voltage Rating 125/250 VAC

Dimensions

| | |
|--------------|-----------------------------|
| Display Size | Standard Sized Product |
| Length | 2.13 in |
| Width | 2.13 in |
| Height | 3.90 in |
| Dimensions | 2.13 in x 2.13 in x 3.90 in |

General

| | |
|-----------------------------------|------------------------------------|
| OEM Brand Name | Hubbell Bryant |
| Style | Internal Cord Clamp |
| Color | Black, White |
| Item Type | 30A Triple Gripper Nylon Connector |
| Insulation | Insulated Body |
| Material - Mounting Hardware Type | Cord Mounted Connector Body |
| Material | Composite |
| UPC | 781786695399 |

Logistics

| | |
|-----------------|------|
| Carton Quantity | 10 |
| Pallet Quantity | 2250 |

Operational

| | |
|--------------------|---|
| Temperature Rating | <ul style="list-style-type: none"> • Maximum Continuous: 75° C • Minimum Continuous: -40° C w/o impact, -25° with impact. |
|--------------------|---|

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)